


prime tac

400 Series

460 | 3.1 Mil Performance Grade BOPP Acrylic Carton Sealing Tape

Our Primetac[™] brand 460 acrylic carton sealing tape is a premium performance grade tape made for an array of heavy duty packaging applications. Ideal cold temperature, refrigerator, and freezer tape.

 PERFORMANCE GRADE




Built for Boxes



Ideal for Cold Temps



UV and Yellowing Resistance



All-Weather



Meets FDA Guidelines for Indirect Food Contact

BUILT FOR



Specifications

Adhesive

Solvent acrylic

Total Thickness

3.1 mil | 80 microns
PSTC-133

Adhesion to Steel

>38 oz / inch (0.4 kg / cm)
PSTC-101

Tensile Strength

28 lbs / inch (5 kg / cm)
PSTC-131

Operating Temperature

20°F - 120°F (-7°C - 49°C)

Features

- ✓ Superior adhesion properties and holding force
- ✓ Meets FDA guidelines for indirect food contact
- ✓ Resistance to yellowing, weathering and aging makes it good for retail packaging in hot or cold temps
- ✓ RoHS & REACH compliant
- ✓ Very long shelf life

Other Physical Properties

Property	Film Thickness	Elongation at Break PSTC-131	Holding on Steel (1/2" x 1/2") PSTC-107	Holding on Linerboard (1" x 1/2") PSTC-107
Standard	2.36 mil	160%	100 ± 20 min.	460 ± 30 min.
Metric	60 microns	160%	100 ± 20 min.	460 ± 30 min.

Test Condition: Temperature: 23°C ± 2°C (73.4°F ± 3.6°F) | Relative Humidity: 50% ± 5%

Applications

- Cartons exposed to UV light
- Heavy weight packages
- Cold storage
- Splicing

Storage and Usage

Suggested Storage Conditions:

- 15°C - 30°C (59°F - 86°F), or as close as possible to room temperature.
- 60% Max Relative Humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

Suggested Application Conditions

- 32°F - 122°F (0°C - 50°C)
- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available Product Options

Stock Lengths



50m

Stock Widths



48mm



72mm

Types



Hand



Machine

Colors

Clear

We customize! Contact a representative for special sizes.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.