



prime tac

700 Series

751 | 9 Mil Industrial Grade Multi-Purpose Duct Tape

Our Primetac[™] 751 premium duct tape is built with a natural rubber adhesive that resists curling for a convenient and reliable application. The 751 also bonds well to most surfaces and has good all-weather performance.

INDUSTRIAL GRADE



Clean Removal



Outdoor Durable



Built for Bundling



Eco-Friendly & Low VOC



Built for Irregular Surfaces

BUILT FOR



Specifications

Adhesive

Natural Rubber

Total Thickness

9 mil | 229 microns
ASTM D-1000

Adhesion to Steel

70 oz / in (7.7 N / cm)
PSTC-101

Tensile Strength

24 lb / in (42 N / cm)
ASTM D-1000

Operating Temperature

40°F - 200°F (4°C-93°C)

Features

- ✓ Good balance of strength and conformability
- ✓ Environmentally friendly & safe to use (Low VOC)
- ✓ Resists moisture, twisting, and curling
- ✓ Bonds well to most surfaces
- ✓ Good all-weather performance

Other Physical Properties

| Property | Backing | Adhesion to Backing PSTC-101 | Elongation ASTM D-1000 | VOC Content |
|----------|-----------------|---------------------------------|---------------------------|--------------|
| Standard | PE Coated Cloth | 40 oz / in | 20% | <3 g/L |
| Metric | PE Coated Cloth | 4.4 N / cm | 20% | <0.37 oz/gal |

Tested in accordance with UL 723

Applications

- Maintenance and general repair
- Plumbing applications
- Bundling, patching and mending
- General purpose abatement

Storage and Usage

Suggested Storage Conditions:

- 16°C - 27°C (60°F-80°F), or as close as possible to room temperature.
- 40-60% max relative humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

Suggested Application Conditions

- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available Product Options

Stock Lengths



55m

Stock Widths



48mm

Types



Hand



Machine

Colors

Silver

We customize! Contact a representative for special sizes and colors.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.