



## prime tac

700 Series

# 752 | 11 Mil Performance Grade Multi-Purpose Duct Tape

Our Primetac™ 752 premium duct tape is built with a natural rubber adhesive that resists curling for a convenient and reliable application. The 752 also bonds well to most surfaces and has good all-weather performance.

 PERFORMANCE GRADE



Clean Removal



Outdoor Durable



Built for Bundling



Eco-Friendly  
& Low VOC



Built for Irregular  
Surfaces

## BUILT FOR



Construction



Abatement/Restoration



Furniture



Auto



Industrial MRO



HVAC

## Specifications

### Adhesive

Natural Rubber

### Total Thickness

11 mil | 279 microns  
ASTM D-1000

### Adhesion to Steel

80 oz / in (8.75 N / cm)  
PSTC-101

### Tensile Strength

26 lb / in (45.5 N / cm)  
ASTM D-1000

### Operating Temperature

40°F - 200°F (4°C-93°C)

## Features

- ✓ Excellent balance of tensile strength and tearability
- ✓ Environmentally friendly & safe to use (Low VOC)
- ✓ Superior holding power for hanging applications
- ✓ Aggressive adhesion to rough surfaces
- ✓ Good all-weather performance

## Other Physical Properties

Property	Backing	Elongation ASTM D-1000	VOC Content
Standard	PE Coated Cloth	21%	<1 g/L
Metric	PE Coated Cloth	21%	<0.16 oz/gal

Tested in accordance with UL 723

## Applications

- Manufacturing maintenance
- Duct sealing & HVAC uses
- Bundling, patching and mending
- General repair

## Storage and Usage

### Suggested Storage Conditions:

- 16°C - 27°C (60°F-80°F), or as close as possible to room temperature.
- 40-60% max relative humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

### Suggested Application Conditions

- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available  
Product Options

## Stock Lengths



55m

## Stock Widths



48mm

## Types



Hand



Machine

## Colors

Silver

**We customize! Contact a representative for special sizes and colors.**

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.