



prime tac

800 Series (Water Activated)

805 | 5.1 Mil Medium Duty (White) Reinforced Water-Activated Tape

Our Primetac™ 805 premium water-activated reinforced kraft paper tape is a great way to get an eco-friendly alternative to pressure sensitive adhesive tape without sacrificing carton sealing effectiveness.

MEDIUM DUTY



Built for Boxes



Fiberglass Reinforced



High Tensile Strength



Pilfer-Proof



Eco-Friendly

BUILT FOR



Retail



Food & Beverage



Packaging



Transportation



Fulfillment



Industrial



Pharma/Medical

Specifications

Adhesive
Starch

Backing
25lb White Kraft Paper (Top & Btm)

Caliper
5.1 mil | 0.13 mm

Tensile Strength
MD: 47 lbs / inch | CD: 25 lbs / inch
ASTM D-3759

Reinforcement
MD: 72mm 110 (1-1-1-1-1)
CD: 25.4mm 150 (1-1-1)

Features

- ✓ Built for recycled corrugated and non-unitized loads
- ✓ Superb tensile strength
- ✓ Works best for light weight to average cartons (<24lbs/11kg)
- ✓ Eco-friendly, pollution-free material and adhesive
- ✓ Get peace of mind with pilfer-proof, tamper evident tape
- ✓ Superior durability to keep tape intact

Other Physical Properties

Property	Tensile (MD) <i>ASTM D-3759</i>	Tensile (CD) <i>ASTM D-3759</i>	Reinforcement (MD)	Reinforcement (CD)
Standard	47 lbs / in	25 lbs / in	72 mm 110 (1-1-1-1-1) Fiberglass	25.4 mm 150 (1-1-1) Fiberglass Diamond Pattern
Metric	8.4 kg / cm	4.5 kg / cm	72 mm 110 (1-1-1-1-1) Fiberglass	25.4 mm 150 (1-1-1) Fiberglass Diamond Pattern

Test Condition: Temperature: 23°C ± 2°C (73.4°F ± 3.6°F) | Relative Humidity: 50% ± 5%

Applications

- Carton sealing
- Packaging
- Security tape

Storage and Usage

Suggested Storage Conditions:


- 4°C - 26°C (39°F-79°F), or as close as possible to room temperature.
- 50% Max Relative Humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

Suggested Application Conditions

- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available Product Options

Stock Lengths



We customize! Contact a representative for special sizes.

Stock Widths



Types



Manual Automatic

Colors

Natural Kraft

White-White

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.