



prime tac

800 Series (Water Activated)

807 | 5.5 Mil Heavy Duty Reinforced Water-Activated Tape

Our Primetac[™] 807 premium water-activated reinforced kraft paper tape is a great way to get an eco-friendly alternative to pressure sensitive adhesive tape without sacrificing carton sealing effectiveness.



Built for Boxes



Fiberglass Reinforced



High Tensile Strength



Pilfer-Proof



Eco-Friendly

BUILT FOR



Retail



Food & Beverage



Packaging



Transportation



Fulfillment



Industrial



Pharma/Medical

Specifications

Adhesive
Starch

Backing
25lb Kraft Paper (Top & Btm)

Caliper
5.5 mil | 0.14 mm

Tensile Strength
MD: 65 lbs / inch | CD: 24 lbs / inch
ASTM D-3759

Reinforcement
MD: 72 mm 75 (1-1-1-1-1)
CD: 28 mm 150 (1-1-1-1)

Features

- ✓ Built for recycled corrugated and non-unitized loads
- ✓ Superb tensile strength
- ✓ Heavy duty and superior durability to keep tape intact
- ✓ Eco-friendly, pollution-free material and adhesive
- ✓ Get peace of mind with pilfer-proof, tamper evident tape

Other Physical Properties

Property	Tensile (MD) ASTM D-3759	Tensile (CD) ASTM D-3759	Reinforcement (MD)	Reinforcement (CD)
Standard	65 lbs / in	24 lbs / in	72 mm 75 (1-1-1-1-1) Fiberglass	28 mm 150 (1-1-1-1) Fiberglass Diamond Pattern
Metric	290 N/25mm	105 N/25mm	72 mm 75 (1-1-1-1-1) Fiberglass	28 mm 150 (1-1-1-1) Fiberglass Diamond Pattern

Test Condition: Temperature: 23°C ± 2°C (73.4°F ± 3.6°F) | Relative Humidity: 50% ± 5%

Applications

- Carton sealing
- Packaging
- Security tape

Storage and Usage

Suggested Storage Conditions:


- 4°C - 26°C (39°F-79°F), or as close as possible to room temperature.
- 50% max relative humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

Suggested Application Conditions

- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available Product Options

Stock Lengths



450ft


1000ft

Stock Widths



72mm

Types



Manual

Automatic

Colors

Natural Kraft

We customize! Contact a representative for special sizes.



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.