



prime tac

800 Series (Masking)

819 | 6 Mil Industrial Grade High Temp Masking Tape

Our Primetac[™] 819 masking tape is a premium industrial grade tape built for packaging, bundling, protection, and holding. The 819 is designed for high temperature resistance of up to 203°F for 30 minutes.

INDUSTRIAL GRADE



Built for Bundling



Ideal for Labeling



High Temperature Resistance



Hand-Tearable



Clean Removal

BUILT FOR



Construction



Appliance



Transportation



Painting



General Industrial



Fulfillment

Specifications

Adhesive

Solvent Natural Rubber

Total Thickness

6 mil | 150 microns
PSTC-133

Adhesion to Steel

32 oz / inch (0.35 kg / cm)
PSTC-101

Tensile Strength

18.7 lbs / inch (3.3 kg / cm)
PSTC-131

Max Temp. Resistance

203°F (95°C) / 30 min

Features

- ✓ Our highest temp. resistance crepe masking tape
- ✓ Strong adhesion and holding power on a variety of surfaces including paper, painted, metal, glass, and wood
- ✓ Clean removal thanks to strong crepe paper backing
- ✓ Resistant to paint bleed-through
- ✓ Quick tack

Other Physical Properties

Property	Backing	Elongation at Break PSTC-131	Application Temperature Range
Standard	Crepe paper	13% ± 5%	50°F - 104°F (10°C - 40°C)
Metric	Crepe paper	13% ± 5%	50°F - 104°F (10°C - 40°C)

Test Condition: Temperature: 23°C ± 2°C (73.4°F ± 3.6°F) | Relative Humidity: 50% ± 5%

Applications

- Paint Masking
- DIY & Decorating
- Bundling, Holding & Splicing
- Woodworking & Metalworking

Storage and Usage

Suggested Storage Conditions:

- 15°C - 30°C (59°F-86°F), or as close as possible to room temperature.
- 60% Max Relative Humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

Suggested Application Conditions

- 50°F - 104°F (10°C - 40°C)
- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available Product Options

Stock Lengths



55m

Stock Widths



24 mm



36 mm



48 mm

Types



Hand



Machine

Colors

Beige

We customize! Contact a representative for special sizes.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.