



## prime tac

900 Series (PVC)

# 900M | 2.2 Mil Performance Grade UPVC Self-Adhesive Tape

Our Primetac<sup>™</sup> brand 900M tape is a premium, heavy duty natural rubber based PVC packaging tape. The aggressive adhesive and high temperature resistance makes this an excellent tape for rough shipping conditions.

 PERFORMANCE GRADE



Built for Boxes



All-Weather



Quick Tack



Superior Package  
Reinforcement



Hand-Tearable

## BUILT FOR



Food & Beverage



Heavy Packages



Bundling/Palletizing



Splicing



Industrial



Carton Sealing

## Specifications

### Adhesive

Solvent Natural Rubber

### Total Thickness

2.2 mil | 56 microns

### Adhesion to Steel

25 oz / inch (0.28 kg / cm)

### Tensile Strength

31 lbs / inch (5.5 kg / cm)

### Operating Temperature

-4°F - 158°F (-20°C - 70°C)

## Features

- Ideal for heavy packages and irregular surfaces
- Suitable for top surface printing
- Highly resistant to moisture, acids, tears and punctures
- High holding power for a wide variety of use cases
- Superior seal performance for rough shipping conditions

## Other Physical Properties

Property	Backing	Film Thickness	Elongation % at Break
Standard	Rigid UPVC	1.4 mil	70% ± 30%
Metric	Rigid UPVC	36 microns	70% ± 30%

Test Condition: Temperature: 23°C ± 2°C (73.4°F ± 3.6°F) | Relative Humidity: 50% ± 5%

## Applications

- Screen printing (block out)
- Heavy weight packages
- Cartons in freezer
- Mounting & splicing

## Storage and Usage

### Suggested Storage Conditions:


- 15°C - 30°C (59°F - 86°F), or as close as possible to room temperature.
- 60% Max Relative Humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

### Suggested Application Conditions

- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.


Available  
Product Options

## Stock Lengths



*We customize! Contact a representative for special sizes.*

## Stock Widths



## Types



## Colors



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warranties or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.