

## prime tac

900 Series (950 for Serrated; 960 for Smooth)

## 950/960 | 7 Mil General Purpose Polyethylene Film Tape

Our Primetac™ 950 and 960 premium polyethylene tapes are strong and highly conformable. They are easy to apply and have excellent adhesion to a wide variety of difficult surfaces such as cement, brick, stone and concrete.

 GENERAL PURPOSE



Clean Removal



Outdoor Durable



Built for Splicing



Hand-Tearable



Built for Irregular Surfaces

### BUILT FOR



Construction



Abatement/Restoration



Safety & Marking



Stucco



Industrial MRO



Convention

### Specifications

#### Adhesive

Synthetic Rubber

#### Total Thickness

7 mil | 178 microns  
PSTC-133

#### Adhesion to Steel

75 oz / inch (0.84 kg / cm)  
PSTC-101

#### Tensile Strength

25 lbs / inch (4.5 kg / cm)  
PSTC-131

#### Operating Temperature

20°F - 200°F (-7°C - 93°C)

### Features

- ✓ Environmentally friendly & safe to use (Low VOC & contains no heavy metals)
- ✓ Excellent shear strength
- ✓ Clean removal allows for repositioning
- ✓ Conformable on irregular surfaces
- ✓ Superb durability and solvent resistance

### Other Physical Properties

Property	Backing	Elongation at Break	Application Temperature Range
Standard	PE Film	85%	30°F - 160°F (-1°C - 71°C)
Metric	PE Film	85%	30°F - 160°F (-1°C - 71°C)

Test Condition: Temperature: 23°C ± 2°C (73.4°F ± 3.6°F) | Relative Humidity: 50% ± 5%

### Applications

- Stucco masking
- Labeling
- Holding & splicing
- Bundling & palletizing

### Storage and Usage

#### Suggested Storage Conditions:

- 15°C - 30°C (59°F - 86°F), or as close as possible to room temperature.
- 60% Max Relative Humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

#### Suggested Application Conditions

- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available Product Options

### Stock Lengths



55m

### Stock Widths



48mm

### Edge Texture



Serrated (950)



Smooth (960)

### Types



Hand



Machine



### Colors

Red

White

More Colors Upon Request

**We customize! Contact a representative for special sizes and colors.**

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.