

prime tac

900 Series (951 for Serrated; 961 for Smooth)

951/961 | 7 Mil General Purpose UV-Resistant PE Film Tape

Our Primetac[™] 951 and 961 premium polyethylene tapes are strong and highly conformable. They are easy to apply and have excellent adhesion to a wide variety of difficult surfaces such as cement, brick, stone and concrete.

 GENERAL PURPOSE



Clean Removal



Outdoor Durable



Built for Splicing



UV Resistance



Built for Irregular
Surfaces

BUILT FOR



Construction



Abatement/Restoration



Safety & Marking



Stucco



Industrial MRO



Convention

Specifications

Adhesive

Synthetic Rubber

Total Thickness

7 mil | 178 microns
PSTC-133

Adhesion to Steel

75 oz / inch (0.84 kg / cm)
PSTC-101

Tensile Strength

25 lbs / inch (4.5 kg / cm)
PSTC-131

Operating Temperature

20°F - 200°F (-7°C - 93°C)

Features

- Short term UV resistance for outdoors up to 28 days
- Clean removal allows for repositioning
- Conformable on irregular surfaces
- Superb durability and solvent resistance
- Environmentally friendly & safe to use (Low VOC & contains no heavy metals)

Other Physical Properties

Property	Backing	Elongation at Break	Application Temperature Range
Standard	PE Film	85%	30°F - 160°F (-1°C - 71°C)
Metric	PE Film	85%	30°F - 160°F (-1°C - 71°C)

Test Condition: Temperature: 23°C ± 1°C (73.4°F ± 2°F) | Relative Humidity: 60% ± 5%

Applications

- Stucco masking
- Labeling
- Holding & splicing
- Bundling & palletizing

Storage and Usage

Suggested Storage Conditions:

- 60°F-80°F (16°C - 27°C) or as close as possible to room temperature.
- 40-60% relative humidity
- Original packaging in a cool, dry area away from direct sunlight exposure and from freezing.

Suggested Application Conditions

- 30°F - 160°F (-1°C - 71°C)
- Surfaces to which tape is applied should be clean, dry and free of dust, grease, oil or other contaminants.

Available Product Options

Stock Lengths



55m

Stock Widths



48mm

Edge Texture



Serrated (951)



Smooth (961)

Types



Hand



Machine



Colors

Red

White

More Colors
Upon Request

We customize! Contact a representative for special sizes and colors.

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are averages obtained from tests recommended by PSTC procedures in our laboratory and the user must by test or otherwise determine suitability for his purpose. There is no warranty of fitness for a particular purpose. Primetac does not take responsibility for the defective material if not stored and used in accordance with the conditions listed above. This specification sheet might change due to the continuous improvement for better quality product.